

SECTIONAL VALVES SD25 Series

Simple, compact and heavy duty design - 1 to 12 sections
 For open and closed centre.
 Fitted with main pressure relief and load check.
 Available with:
 Parallel, tandem or series circuit.
 Optional carry-over port.
 Port Relief and anticavitation circuit valves.
 20mm Ø non-interchangeable spools.
 Manual, electro-hydraulic, hydraulic pilot or remote cable spool control.



Part No.	No. of Spools	Nom. Flow	M W P P,A,B parallel	M W P P,A,B series	M W P T	Dim A	Leakage Per 100 BAR	Tiebolt Torque	Ports BSPP	
		L/Min	BAR	BAR	BAR	mm	cc/Min	NM	P,A,B	T
SD25/1/AC/18/RC	1	240	315	210	25	234	4	50	1"	1 1/4"
SD25/2/AC/2X18/RC	2					296				
SD25/3/AC/3X18/RC	3					358				
SD25/4/AC/4X18/RC	4					420				
SD25/5/AC/5X18/RC	5					482				
SD25/6/AC/6X18/RC	6					544				

The above Model complete with cylinder spools & spring centred. Standard handles included in the price

Options		
Type	Part No.	Description
1,2,3,4		Spool Options - refer to page A 22
11	5V11120000	Detent 3 Position
15	5V15120000	Detent 2 Position 0 & 1
RE	4TAP426612	High Pressure Carry Over
P1,P2	XCAR216116	Port Relief (G3)
U1,U2	X011411100	Port Relief & Anti Cav. (G3)
LCB	5CLO225000	Joystick - Mechanical
8P	5V08120701	Pneumatic Pilot ON/OFF
8PZ	5V08120708	Pneumatic Pilot Proportional
S	SD25-S	Series Section
CS1	SD25/CS1	Mid Outlet
		Cable Control - Please refer to A 44

