



Section 1

Hydraulic Hose

HBR - Hose Bend Restrictor

Description: Flexible hose bend restrictors protect the hose near the couplings. Gates tapered PVC sleeves reduce bending stresses in the hose near the coupling to prevent damage such as in portapower and pressure wash applications. Installed during assembly the product withstands temperatures of -40°F to +200°F (-40°C to +93°C).

Featured benefits:

Tapered design reduces bending stress near the hose coupling junction

Smooth finish will not scratch finish on equipment being washed

Wide temperature range

Friction fit means no adhesive to clamps required to hold bend restrictor in place



Product Specifications

Part Number	ID		Length		Colour	Hose Size & Type
	in	mm	in	mm		
HBR-1050	0.63	16.0	5.50	139.7	Black	4G1, 4G1H, 4G2, 4M3K, 4M2T, 4PC I, 4PC II
HBR-1051	0.73	18.5	6.00	152.4	Black	6G1, 6G1H, 6M3K, 6M2T, 6PC I
HBR-1054	0.77	19.6	7.00	177.8	Black	6G2, 6PC II
HBR-1052	0.84	21.3	7.00	177.8	Black	8G1, 8G1H, 8PC II
HBR-1053	1.00	25.4	8.00	203.2	Black	10G1, 10G1H, 10M2T