



OIL FLOW CAPACITY OF HOSE AND TUBING

INSIDE DIAMETER	SUCTION LINES (-0.25 TO 0 BAR)			HIGH EFFICIENCY LINES (0 TO 35 BAR)			CONTINUOUS RUN LINES (36 TO 207 BAR)			INTERMITTENT RUN LINES (208 BAR & ABOVE)		
	1.2M/SEC LTR/MIN	4FT/SEC US GPM	3M/SEC LTR/MIN	10FT/SEC US GPM	4.5M/SEC LTR/MIN	15FT/SEC US GPM	6.1M/SEC LTR/MIN	20FT/SEC US GPM				
1/4"	2.3	0.6	5.7	1.5	9	2.3	11	3				
5/16"	3.8	1	9	2.4	14	3.6	18	4.8				
3/8"	5.3	1.4	13	3.4	19	5	27	7				
1/2"	9.5	2.5	23	6	34	9	45	12				
5/8"	15	3.8	38	10	53	14	72	19				
3/4"	21	5.5	53	14	79	21	106	28				
7/8"	28	7.5	72	19	107	28	142	37				
1"	38	10	85	25	140	37	185	49				
1 1/4"	57	15	144	38	216	57	231	61				
1 1/2"	83	22	209	55	314	83	416	110				
1 3/4"	114	30	285	75	426	112	570	150				
2"	148	39	371	97	556	147	742	196				
2 1/2"	231	61	579	153	870	230	1158	306				
3"	333	88	832	220	1249	330	1669	441				

Southcott Pty Ltd accepts no liability for any errors or omissions and will not be held liable for any consequential or incidental damages.